

# 12" Signal Backplates

## Vacuum Formed ABS • Non-Louvered

- Vacuum Formed from Black, U.V. Stabilized Optimum-Grade (GPX-3800) ABS
- 5/8" Formed Flange on All Sides Gives Much Greater Rigidity and Structural Integrity
- Nominal Thickness .125"
- 5" Border Encompasses Signal Head
- 3" Corner Radius—All Corners
- Hair Cell Finish Front Side, Smooth Finish on Rear
- Holes are Dimpled—Just Drill and Go!
- Stainless Steel Screws and Washer Tabs provided for Mounting
- Fits also LFE/Mark IV 12" Signals



BP-P-1003GTE

MODEL	DESCRIPTION
BP-P-1001GTE	For 12" Single Section Signal
BP-P-1002GTE	For 12" Two Section Signal
BP-P-1003GTE	For 12" Three Section Signal
BP-P-1004GTE	For 12" Four Section Signal
BP-P-1005GTE	For 12" Five Section Signal, In Line
BP-P-CL50-GTE	For "Doghouse Cluster," Span Wire Mount, 17" C/T/C, 5 Section
BP-P-CL55-GTE	For "Doghouse Cluster," Astro-Brac Mount, 16" C/T/C, 5 Section



**General  
Traffic  
Equipment  
Corporation**

**(845) 569-9000**

**TOLL FREE:**

**(800) 222-2828**

**FAX: (845) 569-1800**

**E-MAIL:**

**gtec corp@aol.com**



**259 Broadway, Newburgh, NY 12550**