Balance Adjuster

BA-12260A

47,000 P/S/I TENSILE STRENGTH!

- Allows any Signal Combination to be hung Plumb
- Precision Die-Cast of High-Strength Aluminum
- Stainless Steel Setscrew and Jam-Nut lock Eye Bolt in Place
- Hardware available in Stainless or Zinc Plated (Standard)
- Pivot holes lined with Corrosion-Resistant, High-Strength Stainless Steel Bushings
- Clevis Pin is ⅝″ Diameter
- Your Choice of Powder-Coated Finishes Available

Please specify powder-coated finish when ordering

General Traffic Equipment's BALANCE ADJUSTER is one of the most useful and practical signal hardware items that has been developed. The BALANCE ADJUSTER is used on span wire and mast arm signal assemblies to assure plumbness when signal faces are not uniform. Maximum visibility is determined when signals are hung at the proper angle. A universal feature of the BALANCE ADJUSTER allows 360° degree signal indexing with a clamp to hold in any position. High strength stainless steel bushings are used in pivot holes to prevent wear and elongation.

General Traffic Equipment Corporation

(845) 569-9000

TOLL FREE: (800) 222-2828

FAX: (845) 569-1800

E-MAIL: gtecorp@aol.com

MADE WITH PRIDE IN THE USA

259 Broadway, Newburgh, NY 12550